




INL3149WU

Native WUXGA Laser projector



Inputs

1. HDMI 1.4
2. HDMI 2.0
3. VGA 1
4. VGA 2
5. S-Video
6. Composite Video
7. 3.5mm Audio/Mic
8. 3.5mm Audio
9. HDBaseT

Outputs

10. USB-A 5v
11. 3.5mm Audio
12. VGA
13. RS232
14. Kensington Lock
15. RJ45



Specifications

Display / Image

Display Technology	DLP
Native Resolution	1920 x 1200 WUXGA
Native Aspect Ratio	16:10
Brightness Lumens	5500
Contrast Ratio	500000:1
Projection Offset (Percentage)	102%
Keystone Correction (Degrees)	±30 Vertical / Horizontal
Image Uniformity (Percentage)	85%

Connectivity

Input Sources	HDBaseT, HDMI x 2, VGA x 2, S-Video, Composite Video, 3.5mm Audio x 2, USB-A
Output Sources	VGA, 3.5mm Audio, USB-A 5v (Service)
Input Control	RJ45, Infrared Remote, RS232
Security	Kensington Lock, Password Protected Interface

Light Source

Type	Laser Quantum Colour Engine
Hours	30000

Audio

Speakers	2
Sound Channel	Stereo
Speaker (Watts)	10

Optical

Throw Ratio	1.4 - 2.24
Throw Distance (Meters)	1.0 - 9.1
Image Size Diagonal (Meters)	0.53 - 7.67
Zoom Type	Manual
Lens Shift	Vertical -95% - 107%
Optical Zoom	1.6:1

Special Features

Image Enhancement	Dynamic Black, IP5x, 5 Laser adjustments, HDR-Image performance
Image Adjustments	4 corner geometric adjustment, Electronic Image shift, Digital zoom, Edge masking, Automatic keystone correction
Image Presents	Presentation, Bright, HDR SIM, Cinema, Game, sRGB, DICOM SIM, User, 3D
Wall Colour Presets	Off, Blackboard, Light Yellow, Light Green, Light Blue, Pink, Gray
Operating Pitch / Roll	Table Top / Ceiling / Portrait / Full 360 degree pitch
Operational Time	24 x 7
Power Saving	Direct power on, Signal power on, Auto power off

Environmental

Power Consumption Minimum / Maximum (Watts)	190 / 341
Standby Power (Watts)	<0.5
Audible Noise (dBA)	27
Maximum Altitude (Meters)	3048
Operating Temperature	5 - 35° C

General

Product Dimensions (Length x Width x Height)	374 x 302 x 117mm
Product Weight (Kilograms)	5.5
Shipping Dimensions (Length x Width x Height)	564 x 468 x 254mm
Shipping Weight (Kilograms)	7.7
OSD Languages	27 languages (English / Deutsch / Français / Italiano / Español / Português / Polski / Nederlands / Hindi / Norsk / Dansk / Svenska / Filipino / Malay / Romanian / 繁體中文 / 简体中文 / 한국어 / العربية / Русский / Magyar / Čeština / ไทย / Türkçe / Vietnamese / Indonesian)
PC / 2D / 3D Compatibility	All standard formats and standards supported
Standard Accessories	User manual (CD), Safety / Registration Card, HDMI Cable, Regional Power

Product specifications are subject to change at any time without notice